OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R76/2006-NL1-14.15
Project number 13200599

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant and Manufacturer	Mettler-Toledo, LLC 1150 Dearborn Drive Worthington, Ohio 43085-6712 United States of America
Identification of the certified type	A **Non-automatic weighing instrument** Type : BC series
Characteristics	See next page

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R76-1, Edition 2006 for accuracy class (III)

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified.
This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority

NMi Certin B.V., OIML Issuing Authority NL1
6 May 2014

C. Oosterman
Head Certification Board

NMi Certin B.V.
Hugo de Grootplein 1
3314 EG Dordrecht
the Netherlands
T +31 78 6332332
certin@nmi.nl
www.nmi.nl

OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R76/2006-NL1-13.42
Project number 13200599

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):
- No. NMi-13200599-01 dated 17 April 2014 that includes 60 pages;
- No. NMi-13200599-02 dated 17 April 2014 that includes 24 pages.

Characteristics of the non-automatic weighing instrument:

Accuracy class	(III)
Maximum capacity	15 kg ≤ Max ≤ 60 kg
Verification scale interval	e ≥ 5 g
Weighing range(s)	Single interval Multi-interval Multiple range
Maximum number of scale intervals	n ≤ 3000 divisions (per partial weighing range)
Maximum number of weighing ranges	2
Tare	T ≤ -Max
Temperature range	-10 °C / +40 °C
Power supply voltage	5 V DC (USB)
Application	Intended to be used for determining a transport tariff
Software identification	30099478 Version 0.00.0002 Checksum: 0x4B8B4440